

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/110697 A2

(51) International Patent Classification⁷:

B23Q 1/00

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/TR2004/000033

(22) International Filing Date: 17 June 2004 (17.06.2004)

(25) Filing Language: Turkish

(26) Publication Language: English

(30) Priority Data:

2003/00903 17 June 2003 (17.06.2003) TR
2004/01403 15 June 2004 (15.06.2004) TR

(71) Applicant and


(72) Inventor: ATAK, Mehmet Salih [TR/TR]; 552/2 Sokak No:1/1 Daire:4 Bornova, 35040 Izmir (TR).

(74) Agent: DESTEK PATENT, INC.; Tophane Ortapazar Cad. No: 7 Osmangazi, 16040 Bursa (TR).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A DEVICE HAVING MULTIPLE DRIVING ARMS ROTATED CIRCULARLY WITHOUT AXIAL ROTATION AND THE METHOD OF THE SAME



WO 2004/110697 A2

(57) Abstract: The present invention relates to a mechanism comprising a number of spindles capable to perform circular motion without an axial rotation drive; and more particularly to a mechanism, which is capable to perform operations such as cleaning, brushing, cutting, boring, abrading, etc. on even or uneven surfaces by means of auxiliary units supplied on terminus of such spindles, and where fluid supply can be made externally for such terminal units.



Published:

- *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.